



TYRE CATALOUGE 2014

CEAT

TRUCK & BUS TYRES

FM-SLEEK

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
7.50 - 20	12	6.0 / 5.5	1775	1555	725	105	655	94



TURBO RIB PLUS

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
8.25 - 20	14	6.5 / 6.0	2230	1960	795	115	725	105



EXTRA MILER

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
9.00 - 20	14	7.0 / 9.5	2570	2255	760	110	690	100



RIB XL

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
9.00 - 20	14	7.0 / 6.5	2570	2255	760	110	690	100



TURBO RIB PLUS

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
9.00 - 20	16	7.0 / 6.5	2650	2325	795	115	725	105



TURBO RIB PLUS

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
9.00 - 20	16	7.5 / 7.0	3000	2630	795	115	725	105



XL SUPER

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
9.00 - 20	16	7.0 / 6.5	2650	2325	795	115	725	105



XL SUPER

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
10.00 - 20	16	7.5 / 7.0	3000	2630	795	115	725	105



CL TROLLA

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
10.00 - 20	16	7.5 / 20	2900	2575	760	110	725	105



CL TROLLA

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
10.00 - 20	18	7.5 / 7.0	2900	2575	760	110	725	105



RIB XL PREMIUM

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
10.00 - 20	18	7.5 / 7.0	3080	2700	825	120	760	110



FM

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
11.00 - 20	16	8.0 / 7.5	3265	2865	795	115	725	105



FM

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
12.00 - 20	18	8.5 / 8.0	3275	3265	795	115	725	105



FM

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
8.25 - 20	14	6.5 / 6.0	2230	1960	795	115	725	105



HCL SUPER

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
8.25 - 20	14	6.5 / 6.0	2180	1900	795	115	725	105



FLEET MASTER

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
9.00 - 20	16	7.0 / 6.5	2575	2240	760	110	725	105



LUG PLUS

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
10.00 - 20	16	7.5 / 7.0	2900	2575	760	110	725	105



XL1

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
10.00 - 20	16	7.5 / 7.0	2900	2575	760	110	725	105



L40

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
10.00 - 20	16	7.5 / 7.0	3000	2630	795	115	725	105



FLEET MASTER

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
10.00 - 20	16	7.5 / 7.0	2900	2575	760	110	725	105



FM

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
11.00 - 20	18	8.0 / 7.5	3250	2800	827	120	758	110



MILE XL RIB

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
9.00 - 20	16	7.0 / 6.5	2650	2325	795	115	725	105



MILE XL RIB

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
10.00 - 20	16	7.5 / 7.0	3000	2630	795	115	725	105



CLT

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
9.00 - 20	14	7.0 / 6.5	2570	2255	760	110	690	100



CLT

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
9.00 - 20	16	7.0 / 6.5	2575	2240	760	110	725	105



HT92

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
9.00 - 20	16	7.0 / 6.5	2650	2325	795	115	725	105



HCL SUPER

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
12.00 - 20	18	8.5	3650	3250	795	115	725	105



FM

Tyre Size	Ply rating	Rim Width (inch)	Maximum Load (Kgs)		Maximum Recommended Pressure (Cold)			
					Single		Dual	
			Single	Dual	(Kpa)	(Psi)	(Kpa)	(Psi)
12.00 - 20	18	8.5 / 8.0	3725	3265	795	115	725	105



**Thanks & Best Regards
Dushan Waduavala**

**Manager – Exports
CEAT Tyres - Sri Lanka
PO BOX 53, Nungamugoda, Kelaniya**

**Mobile :0094713833790 Tel : 0094114822800
E mail : dushan@ceatsrilanka.com Skype : duzhan99
Web : www.ceatsrilanka.com**